


A-A (1:18)



DX1000 Series, Triple oil cleaner

Normal working oil pressure 0.8 to 6 bar

Max. Oil pressure 7 Barg

Design pressure 14 Barg

Removes:

- Particles to 0.1 micron
- Water
- Oxidation bi-products (Sludge & resin)
- Mitigates varnish deposits

PARTS LIST

ITEM	QTY	PART NUMBER	DESCRIPTION	MATERIAL
1	1	T	DX1000 SERIES, MODULE BASED EXTENSION ASSEMBLY FOR SINGLE DOUBLE & TRIPLE STACKED INSERTS	SS316L
A	1	DX1003TP-NVNNN11P	TRIPLE INSERT AIRDRIVEN OIL CLEANER, 0.1 MIC.	SS316L
B	1	PG10SS	10 BAR PRESSURE GAUGE	SS316L
C	1	DX1003	TRIPLE FILTERHOUSING FOR STACKABLE CARTRIDGE ELEMENTS. MAX. PRESSURE, 7 BARG. DESIGN PRESSURE 14 BARG.	SS316L
12	1	2AM-ARVg2	Air driven vane motor & pump, Area Class: II 2 GDc +1 C Ta +40	Fe Painted
13	1	531029	Air regulator for vane motor, MSB4-AGB_C4_J11_M2-WP-EX4-Z. Ex rated with lubricator, shut off valve	Several
22	1	VIS-BSP	DISCHARGE FORM FILTERUNIT, FLOW INDICATOR G3/8" BSPF ALTERNATIVE G1/2"	SS316

Designed by ME	Checked by	Approved by	Date	Date 11.04.2019
--------------------------	------------	-------------	------	---------------------------



EUROPAFILTER NORGE
KEEP IT CLEAN

AIR DRIVEN TRIPLE OIL CLEANER

DX1003TPNVNN11P

Edition
A2019

Sheet
1 / 1